



**AMKAMAC controller A5
smartPanel IP69K.**

For the most extreme conditions.

AMK

The image shows a close-up of the AMKAMAC A5 smartPanel. The panel is dark with a large, bright screen displaying a graphical user interface. A high-pressure water spray is directed at the panel from the right, demonstrating its resistance to high-pressure cleaning. The AMK logo is visible in the top right corner of the panel's frame. The background is a gradient of blue and grey.

AMK

AMKAMAC A5 smartPanel in the highest protection class.

The AMKAMAC A5 smartPanel is a compact machine controller. For the most extreme ambient conditions and highest requirements the AMKAMAC A5 smartPanel is now also available with an IP65/IP69K front panel.





- Suitable for IP69K installation
- Suitable for high-pressure cleaning – even with hot water
- Resistant to dust and aggressive disinfection agents
- In accordance with hygiene standard DIN EN 1672-2
- Multitouch, capacitive touch screen PCT (Projected Capacitive Touch)
- Flush glass front

Controlling Moving Displaying

The powerful machine controller for the demanding machine:

- Real-time Linux
- AIPEX PRO with CoDeSys
- Motion Control technology functions
 - Virtual leading axis
 - Electronic cams
 - Print-mark control
 - Winder functions
 - NC motion
- Visualization with Qt
- Web visualization
- Remote maintenance and diagnostics
- Commissioning function

Technical data

				
Types	A5D-M00-15P	A5D-MC0-15P	A5D-M0E-15P	A5D-MCE-15P
Protection class front/other	IP65/IP69K/IP20			
Touch display	15" color TFT, diagonal: 38.1 cm, XGA 1024x768			
Processor	ATOM with 1.1 GHz			
RAM	512 MByte			
Flash memory	512 MByte			
Non-volatile memory	128 MByte			
Ethernet	1 x 10/100Mbits/s	2 x 10/100Mbits/s	1 x 10/100Mbits/s	2 x 10/100Mbits/s
Fieldbus master	EtherCAT, ACC (CAN)			
Fieldbus slave, optional	-	EtherCAT slave Ethernet/IP slave ProfiNet RT Profibus DP V0	-	EtherCAT slave Ethernet/IP slave ProfiNet RT Profibus DP V0
I/O	-	-	8 digital inputs 24V, 30 μ s, floating 2 digital measuring inputs 24V, 180 ns, floating 4 digital outputs, 24V, 500mA, floating 2 digital outputs 24V, 500mA, floating with time stamp 2 analog inputs \pm 10V with 10V reference voltage output 1 square wave pulse input	
USB	Host and client			
Programming	IEC 61131-3, CoDeSys, optional PLCopen			
Performance	200,000 instructions/ms			
Visualization	Web visu: integrated, Qt: optional			
Ambient temperature	0 - 50°C			
Supply	24VDC, max. 16W	24VDC, max. 19W	24VDC, max. 18W	24VDC, max. 21W
Dimensions WxHxD	410x310x84mm			
Weight	4.5kg			

Fieldbuses and interfaces

- High accuracy synchronization of a large number of axes using only one controller
- Cross-communication in real-time over several levels synchronized with high accuracy
- EtherCAT master and slave (option)
- Data exchange with other programs via OPC server, integration in ERP system
- USB connection
- Multifunctional I/O
- Real-time Linux



Applications

- Packaging industry
- Food industry
- Medical technology
- Beverage industry
- Machine tools
- Woodworking
- Stoneworking

ADVANTAGES

- Easy to clean the machine
- For harsh production environments
- Operation with gloves
- Fanless
- No UPS required
- No rotating components

Control your Motion.



- **AMKAMAC**
controllers
- **AMKASYN**
servo drives
- **DYNASYN**
servo motors
- **AMKASMART**
distributed
drive technology
- **SPINDASYN**
hollow-shaft motors
- **AMKAVERT**
frequency inverters

AMK

AMK Arnold Müller GmbH & Co. KG
Antriebs- und Steuerungstechnik

Postfach 13 55
D-73221 Kirchheim/Teck

Gaussstrasse 37-39
D-73230 Kirchheim/Teck
Phone: +49 (0) 70 21/50 05-0
Fax: +49 (0) 70 21/50 05-199

info@amk-antriebe.de
www.amk-antriebe.de